

[Enlarge](#)

FRONTIER™ 5000 SERIES MULTI

Reliable and Compact Multi-Function Centrifuges Ideal for General Lab Applications

FC5707+R09

Speed Range	200 rpm - 6,800 rpm
Maximum Relative Centrifugal Force	4,445 x g
Maximum Capacity(Rotor)	4x50ml RB/FA or 4x15ml RB/FA
Item Number:	83041073

[REQUEST A QUOTE](#)[ADD TO QUOTE LIST](#)[View All Frontier™ 5000 Series Multi Models](#)

SPECIFICATIONS

Speed Range	200 rpm – 6,800 rpm
Maximum Relative Centrifugal Force	4,445 x g
Maximum Capacity(Rotor)	4x50ml RB/FA or 4x15ml RB/FA
Program memories	99
Rotor In Package	83041009 - Angle rotor 4x50ml RB/FA or 4x15ml RB/FA
Acceleration Gear	10
Deceleration Gear	10
Dimensions	14 in x 9.4 in x 10.9 in (356 mm x 236 mm x 277 mm) (LxHxW)
Display	LCD with backlight

Display	LCD with backlight
Lid lock	Mechanical
Net Weight	22.1 lb (10 kg)
Noise Level	≤60±2 dB(A)
Power	AC Power (Included)
Power Consumption	50 W
Pre-cool time	Not applicable
Rotor Compatibility	Angle rotor 4x50ml RB/FA or 4x15ml RB/FA
Rotor Recognition Method	Manual
Running Time	Continuous; 10 sec to 99 h 59 min 59 sec; Quickspin
Safety Certification	CE; FCC
Working Environment	41°F - 95 °F, 80%RH, non-condensing (5°C – 35°C, 80%RH, non-condensing)