

QUOTATION

Quotation For:

PT Mersi Biovac Proindo

Jalan Raya Pelabuhan No.Km. 18, Cikembar, Kec. Cikembar, Jawa Barat

Ph : -

Fx : -

Email : -

Attn : Mrs Diny

RfQ : NA

Our Ref : SSI.Q2609.436.VF.0128.01

Date : 23 September 2026

PIC : Virgia Febriana

No	Unit Description	Qty	Unit Price	Best Price	Total Price
1	Waterbath Type : BW3-20G (AAH41325K) Brand : Jeiotech Ready Stock Highlight Product • Microprocessor PID control / Automatic tuning / Calibration • Corrosion-resistant stainless steel construction allowing other bath fluids as well as water and silicone fluids • Complete safety protection system with warning alarms. - Low fluid level and dry-running, over-temperature, over-current. Specifications Bath volume (L / cu ft) : 20 / 0.7 Working temperature range (°C / °F) : Amb. +7 to 100 / Amb. +12.6 to 212 Temperature stability at 50°C (±°C / °F) : 0.3 / 0.54 Bath opening / depth (W×L, D) (mm / inch) : 498×300, 200/ 19.6×11.8, 7.9 Exterior with gable cover (W×L×H) (mm / inch) : 564×356×294 / 22.2×14×11.6 Net weight (kg / lbs) : 18.5 / 40.8 Electrical requirements (230V, 50 / 60Hz) : 8.7A Included • Transparent Polypropylene Gable Covers, AAA45533 (indent 2-3 months) • Test Tube Racks Ø16mm for 68 test tubes, AAA45556 (indent 2-3 months) • IQ/OQ • Calibration of KAN This unit is backed up by 1-year official warranty	1	Rp 56,350,000	Rp 31,000,000	Rp 31,000,000



2 **Mannifold Set Pump** 1 Rp 64,638,889 Rp 51,711,111 Rp **51,711,111**

Type : BioVac330B

Brand : Wiggins

Indent 8-12 weeks

Highlight Product

- Manifold are made of SS316 which are excellent chemical resistant and can be fast sterilized by autoclaving
- Maintenance-free
- **Application: Normal liquid filtration; Microorganism determination**

Specifications

Max. Flow Rate (L/min)	: 34
Ultimate Vacuum(mbar)	: 150
Waste Bottle (Capacity in mL/ Material)	: 3000, PC
Number of Branches	: 3
Manifold Material	: Stainless Steel
Filter Diameter (mm)	: 47 / 50
Filter Cup (Capacity in mL/ Material)	: 100 Stainless Steel
Effective Filtration Area(cm ²)	: 9.6
Tube I.D. (mm)	: 8

Included

- Oil-Free Vacuum Pump V400, 167400
- Manifold BioVac330 3-branch Stainless steel, 167103-23
- Filter cups 3 x 100 mL Stainless steel, 167103-61
- Waste Bottle 3000 mL / PC, 167200-33
- Filter Membranes Pall GN-6 MCE / 0.45µm 200 pcs, 167100-52
- Silicon Tube 2 x 1m, 168021-01

This unit is backed up by 1-year official warranty



3 **Binocular Microscope** 1 Rp 65,040,088 Rp 47,000,000 Rp **47,000,000**

Built-in Camera & Tablet

Type : B-290TB

Brand : Optika

Ready Stock

Highlight Product

Built-in camera and digital imaging unit with N-Plan objectives, rackless stage and exclusive X-LED for unmatched performance in illumination. Ideal for discussion group with 360° rotating digital imaging unit.

Specifications

Observation mode	: Brightfield
Head	: Binocular, 360° rotating and 30° inclined. Interpupillary distance from 48 to 75 mm; dioptic adjustment on left eyepiece. Built-in 3.1 MP camera.
Dioptic adjustment	: On the left eyepiece tube
Eyepieces	: WF10x/20 mm, high eye-point and secured by screw.
Nosepiece	: Quadruple revolving nosepiece, rotation on ball b



Page 2 of 4

021-58905002 

info@sentra-sains.com 

Gedung The Bellezza BSA LT 1 SA1-06
Jl. Letjen Soepeno Permata Hijau RT.004 RW.002
Grogol Utara Kebayoran Lama
Jakarta Selatan 12210 

Objectives	: N-PLAN 4x/0.10 N-PLAN 40x/0.65 All with anti-fungus treatment	N-PLAN 10x/0.25 N-PLAN 100x/1.25 (Oil/Water)
Specimen stage	: Double layer rackless mechanical sliding stage, 150x139 mm, 75x33 mm X-Y movement range. Vernier scale on the two axes, accuracy: 0.1 mm.	
Focusing	: Coaxial coarse and fine focusing mechanism with limit stop to prevent the contact between objective and specimen. Adjustable tension of coarse focusing knob	
Condenser	: Abbe N.A. 1.25, with objective-coded iris diaphragm, focusable and centerable.	
Illumination	: X-LED3 type with white 3.6 W LED (6,300 K) and light intensity control. Multi-plug 100-240Vac/6Vdc external power supply.	

Included

- IQ/OQ
- Software

This unit is backed up by 1-year official warranty

4	Vortex Mixer	1	Rp	4,080,556	Rp	3,264,444	Rp	3,264,444
----------	---------------------	----------	-----------	------------------	-----------	------------------	-----------	------------------

Type : Vortex3000 (360115)

Brand : Wiggins

Ready Stock

Specifications

Motion	: Orbital
Speed Range (rpm)	: 0 - 3,000 (Turning knob scale display)
Control	: Scale
Shaking Throw (mm / inch, Ø)	: 4 / 0.16
Operating Mode	: Touch, Continuous
Motor Rating Input / Output (W)	: 12 / 6
Motor	: BLDC motor
Max. Load (kg / lbs) - incl. attachment	: 0.5 / 1.1
Material Body	: Polypropylene
Material Platform	: Silicone rubber
Dimension (WxDxH)	: 148x159x77 mm
Net Weight (kg)	: 2.6
Safety Device	: Current limit protection
Protection Class (DIN EN 60529)	: IP 42

Included

- Platform (pop-off), V0058

This unit is backed up by 1-year official warranty



Price	Rp	132,975,556
Tax 11%	Rp	14,627,311
Total Price	Rp	147,602,867

Page 3 of 4

021-58905002 

info@sentra-sains.com 

Gedung The Bellezza BSA LT 1 SA1-06
Jl. Letjen Soepeno Permata Hijau RT.004 RW.002
Grogol Utara Kebayoran Lama
Jakarta Selatan 12210 

Note

Prices: Price quoted is Franco Jabodetabek and Sukabumi, installation and training included

Delivery: 7-14 days after received of PO (Ready Stock)
8-12 weeks after received of PO (Indent)

Term of Payment: After Delivery (Ready Stock)
50% Down Payment, 50% After Commisioning (Indent)

Validity: This quotation is valid for 14 days as from the above date

Sincerely Yours,**Virgia Febriana**

081110129919

virgia@sentrasains.com